



MASONRY WALL DETAIL AT WF COLUMNS

SCALE: 1 1/2" = 1'-0"

NOTES:

1. TYPICAL AT COLUMNS IN EXTERIOR MASONRY WALLS. COORDINATE WITH ARCHITECTURAL DRAWINGS.
2. USE BITUTHENE 3000 WATERPROOFING MEMBRANE BY W.R. GRACE OR ACCEPTED EQUIVALENT. COVER FULL HEIGHT OF COLUMNS AND OVERLAP WITH FLASHINGS.
3. SEE ARCHITECTURAL DRAWINGS FOR ADDITIONAL INFORMATION.

NOTES TO ENGINEER:

1. USE THIS SECTION FOR TYPE III HYBRID.
2. MODIFY VENEER ANCHORS FOR SEISMIC DESIGN CATEGORY C. ADD VENEER JOINT REINFORCING FOR SEISMIC DESIGN CATEGORIES D, E, OR F.



RYAN-BIGGS ASSOCIATES, P.C.

291 River Street p 518 272.6266
 Troy, NY 12180 f 518 272.4467
 www.ryanbiggs.com

SUBJECT: TYPE III HYBRID

PAGE: C-3

JOB NO.: 9128
 PROJECT: HYBRID MASONRY

DATE: 8/22/08
 BY: DTB